



SPECIFICATIONS

- Submersible up to 5m (15ft)
- Manufactured from 14g 316 Marine Grade Stainless Steel (available in Aluminium)
- Seams continuously welded and ground smooth
- Single piece Neoprene gasket
- 316 Stainless Steel Hardware & Fasteners
- Mounting brackets on enclosure rear for mounting
- Grounding stud on enclosure body for earthing & grounding
- Weld studs for optional internal backing plates & terminal blocks
- High Impact & Crush Resistance

ACCESSORIES

- Internal Mount/Back Plates
- External ground mounting stand
- Custom entry holes
- IP68 Stainless Steel cable glands / chord grips
- EMC / EMI / RFI Shielding (MIL-STD-285)
- Hinged Lid
- Hinged Internal Lid
- Welded in place Threaded Bosses
- Finish options available
- Shock & Vibration Protection (MIL-STD-810)
- Optical Viewing Window

INDUSTRY STANDARDS

Meets IP68 requirements

NEMA 4,4X,6P and IP66, 67, 68

APPLICATION

SLAYSON Submersible **Compact Series** offers IP68 protection against water and dust ingress at depths up to 5m (15ft). Submersible Standard Enclosures are manufactured as standard from 14g Marine Grade 316 Stainless Steel, ensuring protection in harsh and corrosive environments.

MODIFICATION AND CUSTOMISATION

SLAYSON excels at modifying and customizing all our products to meet your exact specifications. Contact our experienced Engineers about your project specific solution.

PART NUMBER	A	B	C	D Mount	E Mount	BACK PLATE PART NUMBER	Height:	Width:	Gauge	Weight (kgs)
	Height: (mm)	Width: (mm)	Depth: (mm)	Height: (mm)	Width: (mm)		(mm)	(mm)		
ASM505020	500	500	200	400	550	ASPI1616	400	400	14	11
ASM505015	500	500	150	400	550	ASPI1616	400	400	14	11
ASM454520	450	450	200	350	500	ASPI1414	350	350	14	11
ASM454515	450	450	150	350	500	ASPI1414	350	350	14	10
ASM404020	400	400	200	300	450	ASPI1212	300	300	14	10
ASM404015	400	400	150	300	450	ASPI1212	300	300	14	9
ASM353520	350	350	200	250	400	ASPI1010	250	250	14	9
ASM353515	350	350	150	250	400	ASPI1010	250	250	14	8
ASM303020	300	300	200	200	350	ASPI0808	200	200	14	8
ASM303015	300	300	150	200	350	ASPI0808	200	200	14	7
ASM252520	250	250	200	150	300	ASPI0606	150	150	14	7
ASM252515	250	250	150	150	300	ASPI0606	150	150	14	6